

APPLICANT: KNEE, Michael et al.
SERIAL NO.: US 10/527,911
FILED: 11/07/2005
Page 3

AMENDMENTS TO THE CLAIMS

Please amend the claims as follows.

1. (currently amended) A method of segmenting image data having a plurality of feature values at each pixel in a sequence of pictures, the feature values including pixel values and motion vector values, comprising:
 - representing the data as points in a segmentation vector space which is the product of the vector space of feature values and the vector space of pixel addresses,
 - representing segments as locations in the segmentation vector space, and
 - determining the membership of a segment for each pixel by the distance in segmentation vector space from the data point representing the pixel to the location of the segment, said distance in segmentation vector space including a displaced frame difference calculated by applying a motion vector from the segment to the pixel.
2. (original) A method according to Claim 1, in which the segments are represented as points.
3. (original) A method according to Claim 1, in which the segments are represented as linear functions mapping the vector space of pixel locations to the vector space of pixel values.
4. (original) A method according to Claim 1, in which the distance measure is a Euclidean distance.
5. (original) A method according to Claim 1, in which the distance measure is a Manhattan distance.

APPLICANT: KNEE, Michael et al.
 SERIAL NO.: US 10/527,911
 FILED: 11/07/2005
 Page 4

6. (original) A method according to Claim 1, in which the coordinate axes are scaled to equalize the variances of the data along each axis.
7. (original) A method according to Claim 1, in which the coordinate axes are scaled in order to minimize the product of errors evaluated along each axis, with the constraint that the scaling factors sum to a constant value.
8. (original) A method according to Claim 1, in which the distance measure is a Mahalanobis distance.
9. (currently amended) A method according to Claim 1 ~~of segmenting image data having a plurality of feature values at each, further comprising the steps of representing the data as points in a segmentation vector space which is the product of the vector space of feature values and the vector space of pixel addresses; representing segments as locations in the segmentation vector space;~~
determining a covariance matrix of the image data in each segment; and
measuring a distance in segmentation vector space of each pixel to each segment location taking into consideration said covariance matrix and determining the membership of a segment for each pixel through said distance measure.
10. (original) A method according to Claim 9, where the covariance matrix Λ of the data in the segment is given by

$$\Lambda_{ij} = \frac{1}{K_S - 1} \sum_{k \in S} (x_{ik} - \mu_i)(x_{jk} - \mu_j)$$

where $(x_1, x_2, \dots, x_N)_k, k \in S$ are vectors in the multidimensional space belonging to segment S , and the location of the segment is given by

$$(\mu_1, \mu_2, \dots, \mu_N) = \frac{1}{K_S} \sum_{k \in S} (x_1, x_2, \dots, x_N)_k$$

where K_S is the number of points in segment S .

11. (original) A method according to Claim 10, wherein the distance measure is equal to

$$(\mathbf{x} - \boldsymbol{\mu}) \cdot \boldsymbol{\Lambda}^{-1} \cdot (\mathbf{x} - \boldsymbol{\mu})^T.$$

12. (currently amended) A method according to Claim 1, ~~of segmenting video data having a plurality of feature values at each pixel in a sequence of pictures, in which the data is represented as points in a segmentation vector space which is the product of the vector space of feature values and the vector space of pixel addresses, and wherein segments are represented as locations in the segmentation vector space, the method comprising the step steps for each picture of initially assigning pixels to segments according to the segment membership of the respective pixel in the preceding picture in the sequence; calculating the location in segmentation vector space for each initial segment utilising feature values from the current picture and determining the membership of a segment for each pixel according to the distance in segmentation vector space from the data point representing the pixel to the location of the segment.~~

13-20. (canceled)

21. (original) A method of segmenting image data having a plurality of feature values at each pixel, comprising the steps of

representing the image data as points in a segmentation vector space which is the product of the vector space of feature values and the vector space of pixel addresses in a toroidal canvas;

initially assigning pixels to segments represented as locations in the segmentation vector space, and

determining the membership of a segment for each pixel according to a distance measure from the data point representing the pixel to the representation of the segment.

APPLICANT: KNEE, Michael et al.
SERIAL NO.: US 10/527,911
FILED: 11/07/2005
Page 6

22-23. (canceled)

24. (previously amended) A method according to Claim 1, in which each pixel is chosen to be a member of a single segment determined by minimizing the distance measure.

25. (previously amended) A method according to Claim 1, in which the number of segments is chosen by the user.

26. (previously amended) A method according to Claim 1, in which the number of segments is chosen as a function of the input data.

27. (previously amended) A method according to Claim 1, in which the number of segments is chosen so that the variance of an overall error measure approaches a predetermined value.

28. (previously amended) A method according to Claim 1, in which two or more parallel versions of the algorithm are run with different numbers of segments and the number of segments chosen is based on the relative performance of the two versions.

29. (previously amended) A method according to Claim 1, in which the representations of segments in the vector space are updated according to the segment membership of pixels.

30. (previously amended) A method according to Claim 1, in which the processes of assigning pixels to segments and of updating the representations of segments are repeated alternately.

31. (previously amended) A method according to Claim 1, in which the initial segmentation is taken from the previous picture in a sequence of pictures.

APPLICANT: KNEE, Michael et al.
SERIAL NO.: US 10/527,911
FILED: 11/07/2005
Page 7

32. (currently amended) A method according to Claim 1 ~~Claim 23~~, in which the displaced frame differences are calculated by applying motion vectors derived from the current state of the segmentation to the input pixel data.

33. (canceled)